Work Gloves SG A187







TOWA

Description	Seamless glove with nitrile foam coating
Material	Liner: Polyester (13 gauge), dual-colour Coating: Nitrile foam, sandy
Application areas	Assembly, industry, construction, etc
Product advantages	High-quality nitrile coating, thus very good mechanical properties (abrasion), oil-resistant Palm in "MicroFinish™" (surface resembles suction cups), thus particular good grip Touchscreen compatible Very good dexterity and well-known TOWA-shape
Single packaging	Headercard
Standards	CAT II, EN ISO 21420:2020, EN 388:2016+A1:2018

Logistical Data

Item no.	Size	Barcode	MOQ	Packaging Unit	Pal
805.100.001M	M / 8	4018653265857	6 Pair	1/6/144	1440
805.100.001L	L / 9	4018653265864	6 Pair	1/6/144	1440
805.100.001XL	XL / 10	4018653265871	6 Pair	1/6/144	1440
805.100.001XXL	XXL / 11	4018653265888	6 Pair	1/6/144	1440

Certification

Feature	Level	Range
Abrasion resistance	3	Min 0 / Max 4
Cut resistance (Coupe-Test)	1	Min 0 / Max 5
Tear resistancet	2	Min 0 / Max 4
Puncture resistance	1	Min 0 / Max 4
Cut resistance (ISO 13997)	X	A-F (X = not tested)

Rating	Range (• - •••••)
Durability	••••
Dexterity	••••
Moisture protection	••
Grease/Oil resistance	••••
Slip resistance	•••••
Breathability	••••